Kube-Sky-RHT-PM0440

Kube-Sky-RHT-PM0440 is a wireless indoor temperature, humidity and 0.4...40 μm size particulate matter transmitter. With it's simple look, Kube-Sky-RHT-PM0440 will look great in e.g. office spaces.

Kube-Sky-RHT-PM0440 uses LoRa technology which enables very long-range radio coverage. This model must be powered from an external supply.

Typically used with Nokeval Sky-radio base station but can also be integrated to systems with RS485 Modbus RTU.



General Specifications

Storage temperature	-30+60 °C, non-condensing
Operation temperature	0+60 °C
Operation humidity	0100 %RH, non-condensing
Protection class	IP20
Enclosure material	Plastic (PC+ABS)
Dimensions	95 mm x 75 mm x 87 mm, Wall mount +1 mm
Weight	270 g

Radio Specifications

Nokeval radio type	Sky-radio
Antenna	Internal
Center requency	433.3434.5 MHz user adjustable
Bandwidth	max 300 kHz OBW, all transmissions fit within 433.05-434.79 MHz
Transmitting power	max 10 dBm E.R.P.
Open space range	up to 5 km
Indoor range	30 to 300 m typically with default Effort setting

External supply with USB

Connector	Micro USB type B 5 ±0.5 V max 200 mA, no suspend function

External supply with a cable

Connector	Push-in spring connector for 0.2-0.5 mm2 conductors
Voltage	5 ±0.5 V DC
Consumption	Average about 3 mA, momentarily max 200 mA







Kube-Sky-RHT-PM0440

Temperature measurement

Measurement range	-20+50 °C
Accuracy	\pm 0,5 °C in the range of +10+50 °C
Step response time	Approx. 45 mins to 90% of step change, still air

Humidity measurement

Measurement range	0100 %RH non-condensing
Accuracy	Typically ±3 %RH at humidity of 2080 %RH and at temperature of +15+30 $^{\circ}\text{C}$

PM0440 measurement

Measurement range	02.8 million particles per litre (up to 10,000 particles per second)
Particle sizes	0.440 µm
Particle type	For max accuracy, assumed to be spherical, density 1.65 g/ml, refractive index 1.5
Values measured	PM1, PM2.5, PM4, PM10, non-standard PM40, raw counts for 24 size bins
PM10 range	0.011 500 000 μg/m3

